

Local Phone: 203-575-9220

PRODUCT DATA SHEET

Business Hours: 8 am - 5 pm

Toll Free: 1-800-537-7663

2001 INC.  
P.O. BOX 2557 WATERBURY, CT 06723-2557  
325 THOMASTON AVE.  
WATERBURY, CT 06702

Emergency Telephone  
1-800-255-3924

PDS Date 8/9/04

Supersedes All Previous Publications

Page 1 of 1

=====SECTION I PRODUCT INFORMATION=====

PRODUCT NAME: **6" OR 7" ZIP TAPE FLASHINGS**

TECHNICAL DATA		
<b>Physical Properties</b>		
	<i>Typical</i>	<i>Test Method</i>
Base Polymer	EPDM	FTIR
Color	Black	Visual
Permeability	0.6 Perm-Mils	ASTM E 96
Hardness	110 dmm	ASTM D 217
Ash Content	16%	ASTM D 297
Peel Strength on EPDM*	5 pli @ 70°F	ASTM D 413
Shear Strength on EPDM *	20 psi @ 70°F	ASTM D 816
Brittleness Temperature	-50°F	ASTM D 746
Solids Content	98%	ASTM C 681
Tensile Adhesive Strength	35 psi (alum.)	ASTM C 907
Tensile Strength (tape)	40 psi min.	ASTM D 412
Elongation (tape)	>1000%	ASTMD 412
Specific Gravity	0.97	ASTM D 71
<b>Applications Properties</b>		
Service Temperature	-40°F to 250°F	ASTM D 3359
Application Temp.	40°F to 120°F	ASTM C 603
Storage Temperature	68°F to 120°F	ASTM D 1337
Minimum Shelf Life	Two Years	ASTM D 1337
* Primed with 2001, Inc. Talc Eater		
NOTE: The foregoing information is published as general information only. The listed properties and performance characteristics are approximate values and are not part of the product specification.		
DISCLAIMER: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations. Prepared By: 2001 Inc.		